

GS 700-E STRAIGHT GRINDER



A small and high-output power package. For milling and grinding work.

Art. No. 0702 520 0

P. Qty. 1

Compact and lightweight

Thanks to the new lightweight construction of the machine.

Convenience and safety

- Safety switch-off: When the tool is locked, the power supply is cut off immediately.
- Restarting protection: Against unintended restarting of the machine.
- Thermal overload protection: Switch-off carbon brushes for motor protection.

Long service life

Impervious to dust thanks to coated field coils and protective grid over winding.

3-year guarantee

On manufacturing and material defects.

Scope of delivery		
Designation	Art. No.	P. Qty.
GS 700-E Straight Grinder	0702 520 X	1
Clamping Jaw Set, 6 mm	0702 520 002	1
Open-Ended Wrench, size 19 mm	0708 522 020	1
Open-Ended Wrench, size 13 mm	0708 522 021	1

Technical Data	
Power consumption	710 W
Output	430 W
Nominal speed	13,000 - 34,000 rpm
Drive for flexible shaft	No
Long neck	No
Rubber protective cap	No
Additional handle	No
Clamping frame (suitable for)	No
Planetary gear	No
Voltage	230 V/50 Hz
Protection class	□ II
Clamping bore of the clamping jaw	6 mm
Cable length	4 m
Dimensions (L x W x H)	327 x 60 x 57 mm
Weight	1.7 kg

Accessories		
Designation	Art. No.	P. Qty.
Clamping Jaw Set, 3 mm	0702 520 001	1
Clamping Jaw Set, 6 mm	0702 520 002	
Clamping Jaw Set, 8 mm	0702 520 003	

Field of application:

For milling and grinding work.

Available in the fleet management system ORSY® fleet.